

SPECIFICATION

Quality		: TATU
Product Definition		: Tufted Loop Pile
Gauge		: 1/10"
No. Of Tufts	ISO 1763	: 195000 / m ²
Pile Fibre		: 100 % Polypropylene
Pile Weight		: 400 gr/m ²
Pile Height	ISO 1766	: 2.9 mm
Primary Backing		: PA/PES non-woven
Tile Backing		: Polyflex with a non-woven fabric
Total Thickness	ISO 1765	: 5.9 mm
Total Weight		: 3700 gr/m ²
Tile Size		: 50 x 50 cm
Tiles Per Box		: 20

PERFORMANCE

Use Classification		: Light Contract Class 2
Abrasion	DIN 54322	: Pass
Vettermann Test	DIN 54322	: Pass
Dimensional Stability	EN 986	: Pass
Thermal Isolation	ISO 8302	: 0.10 m ² K/W

ELECTROSTATIC PROPERTIES

Static Loading		: Anti-Static
----------------	--	---------------

FLAME PROPERTIES

Hot Metal Nut Test	BS 4790	: Low Radius
--------------------	---------	--------------

COLOR STABILITY

Light	ISO 105 B02	: 4.4
Rubbing, Dry	ISO 105 X12	: 5.0
Rubbing, Wet	ISO 105 X12	: 5.0
Shampoo	BS 1006	: 4.8
Water	ISO 105 E01	: 4.5



ISO 14001:2004
ISO 9001: 2008